

SOILCHECK PTY LTD

ABN 89 003 903 517 ACN 003 903 517
DRILLING AND TESTING SERVICES

JK250



	JK250 (Nissan UD) YNW208
DIMENSION / RIG TYPE	TRACKED
A HEIGHT FOR WORK (mast vertical, ground surface horizontal – add up to 1 metre for slopes up to 1:10 or 6 deg)	4.1m
B HEIGHT FOR TRAVEL ON SITE (mast horizontal)	2.2m
C HEIGHT FOR TRAVEL ON ROAD (mast horizontal, including truck)	3.4m
D WIDTH FOR TRAVEL ON SITE (see note below regarding safe work) *	1.51m
E RIG LENGTH FOR TRAVEL ON SITE (mast horizontal)	3.3m
F LENGTH FOR TRAVEL ON ROAD (including truck)	7.8m
G WORKING RIG LENGTH (mast vertical) **	3.1m
SUITABLE UP TO DEPTH ***	40m
WEIGHT OF RIG ON SITE	3.6t + equip
REGISTERED VEHICLE WEIGHT (TARE)	4.1t
MAX WEIGHT ON ROAD (GVM)	10.4t

Notes

- * All Rigs Room to move around equipment for safe operation is required. Additional 2m required if recirculation of drilling mud is required when coring.
- ** All Rigs Space is required for equipment handling during operation. Note also that length required for unloading = travel length + rig length + ramp length.
- *** All Rigs May require support truck for equipment in excess of standard equipment load. Remember to consider this when quoting.

115 Wicks Road Macquarie Park NSW 2113 • Tel: 02 9888 5000 • Fax: 02 9888 5001