SOILCHECK PTY LTD

ABN 89 003 903 517 ACN 003 903 517 DRILLING AND TESTING SERVICES

JK305



	JK305 (Isuzu 900) BG28EF
DIMENSION / RIG TYPE	TRACKED
A HEIGHT FOR WORK (mast vertical, ground surface horizontal – add up to 1 metre for slopes up to 1:10 or 6 deg)	6.2m
B HEIGHT FOR TRAVEL ON SITE (mast horizontal)	2.5m
C HEIGHT FOR TRAVEL ON ROAD (mast horizontal, including truck)	3.8m
D WIDTH FOR TRAVEL ON SITE (see note below regarding safe work) *	1.7m
E RIG LENGTH FOR TRAVEL ON SITE (mast horizontal)	6.7m
F LENGTH FOR TRAVEL ON ROAD (including truck)	10.3m
G WORKING RIG LENGTH (mast vertical) **	5.9m
SUITABLE UP TO DEPTH ***	80m
WEIGHT OF RIG ON SITE	5.3t + equip
REGISTERED VEHICLE WEIGHT (TARE)	7.2t
MAX WEIGHT ON ROAD (GVM)	16.0t

Notes

* All Rigs * All Rigs

All Rigs

Room to move around equipment for safe operation is required. Additional 2m required if recirculation of drilling mud is required when coring. Space is required for equipment handling during operation. Note also that length required for unloading = travel length + rig length + ramp length.

May require support truck for equipment in excess of standard equipment load. Remember to consider this when quoting.